


NANLITE

PavoSlim 120C パネルライト



PavoSlim 120C

ライト本体のみ

Distance	0.5M	1M	3M
2700K	29550 lux / 2745 fc	10500 lux / 975 fc	1388 lux / 129 fc
3200K	31750 lux / 2950 fc	11200 lux / 1040 fc	1475 lux / 137 fc
5600K	36240 lux / 3367 fc	12830 lux / 1192 fc	1675 lux / 156 fc
7500K	34450 lux / 3200 fc	12240 lux / 1137 fc	1594 lux / 148 fc
R	15500 lux / 1440 fc	5100 lux / 474 fc	641 lux / 60 fc
G	27300 lux / 2536 fc	8655 lux / 804 fc	1063 lux / 99 fc
B	3830 lux / 356 fc	1290 lux / 120 fc	156 lux / 14 fc

ソフトボックス&ライトディフューザー装着時

Distance	0.5M	1M	3M
2700K	17360 lux / 1613 fc	4850 lux / 451 fc	579 lux / 54 fc
3200K	18570 lux / 1725 fc	5191 lux / 482 fc	621 lux / 58 fc
5600K	21320 lux / 1981 fc	5944 lux / 552 fc	711 lux / 66 fc
7500K	20050 lux / 1863 fc	5624 lux / 522 fc	670 lux / 62 fc
R	9150 lux / 850 fc	2573 lux / 239 fc	296 lux / 27 fc
G	16680 lux / 1550 fc	4536 lux / 421 fc	536 lux / 50 fc
B	2590 lux / 241 fc	780 lux / 72 fc	90 lux / 8 fc

ソフトボックス&標準ディフューザー装着時

Distance	0.5M	1M	3M
2700K	10420 lux / 968 fc	2460 lux / 229 fc	290 lux / 27 fc
3200K	11160 lux / 1037 fc	2635 lux / 245 fc	312 lux / 29 fc
5600K	12720 lux / 1182 fc	3026 lux / 281 fc	357 lux / 33 fc
7500K	12050 lux / 1119 fc	2856 lux / 265 fc	337 lux / 31 fc
R	5650 lux / 525 fc	1334 lux / 124 fc	161 lux / 15 fc
G	10120 lux / 940 fc	2380 lux / 221 fc	281 lux / 26 fc
B	1650 lux / 153 fc	375 lux / 35 fc	53 lux / 5 fc